

Project name:	
Location:	
Item#: QTY:	
Model#:	

Gas Liquid Propane Pasta Cooker

Model: FLM-PC11-LP



- Open pot structure, transfers heat to plates located strategically outside of the water tank.
- Intense heat rapidly heats the stainless steel sides and the water inside of the water tank.
- Behind the door snap action millivolt control, Doesn't require electric connection.
- The temperature control range 86°F-257°F (30°C-125°C).
- Over temperature protection on 260°F (127°C), more than it, cut off gas.
- · Four stainless steel adjustable legs.
- Large cold zone. captures and holds particles out of the heating zone, reduces taste transfer.
- The pasta cookers are among the industry's most reliable and trusted equipment with highly efficient burners and a variety of basket configurations.
- They can be used to cook fresh or dry pasta.
- This appliance is manufactured for commercial installation only, not intended for home use.
- Gas connections 3/4" Male NPT. Supply gas pressure not to exceed 14" W.C.(1/2 PSI).
- An adequate ventilation system is required for Commercial Cooking Equipment.
- Water connection 1/2"Male NPT.
- Waste water drain connection 1"Male NPT.
- Require a 6" clearance at both side and rear adjacent to combustible construction

Toll Free: +1(800)373-8699 flamaster@chefmindgroup.com
Address: 1189S Jellick Ave,
City of Industry, CA 91748











Toll Free: +1(800)373-8699 flamaster@chefmindgroup.com Address: 1189S Jellick Ave, City of Industry, CA 91748

Gas Liquid Propane Pasta Cooker

Model: FLM-PC11-LP

·CSA design certified NSF listed

MODEL	GAS TYPE	GAS PRESSURE	TOTA BTU	WATER CAPACITY	OVERALL DIMENSIONS	NET WEIGHT	PACKAGE SIZE	Shipping Weight
FLM-PC11-LP	Liquid Propane	10" W.C.	122,000	11 gallons	15½ x 30⅓ x 45¾o	149 lbs.(68 kg)	16¾ x 32¾ o x 33½	167 lbs.(76 kg)













