

| Project name : | oject name : | | | |
|----------------|--------------|--|--|--|
| Location : | | | | |
| Item#: QTY: | | | | |
| Model#: | | | | |

26 3/16" Reach-in Freezer all Stainless Steel

Model: PLM-19FS



- Tested to NSF Standard 7 requirements for open food storage.
- Interior cabinet is full stainless steel, floor with coved corners.
- Exterior cabinet construction consists of full stainless steel front and sides.
- Bottom mounted compressor for more efficient operation in coolest area of kitchen.
- Electronic thermostat with external digital LED display for accurate control and easy reading.
- Larger fan motors and blades for more efficient air flow ensuring faster recovery times.
- Efficient condensate hot gas loop built into condensate pan for energy saving evaporation of excess condensate water.
- Environmentally friendly R290 Hydrocarbon gas.
- 3 adjustable, heavy-duty expoxy coated wire shelves.
- Freezer door frame has integral factory installed heating element to eliminate condensation.
- Self closing doors that remain open at 90 degrees.
- Magnetic door gasket is removable and replaceable without tools.
- Lockable door with foamed-in-place recessed handle.
- Front accessible, bottom mounted condensing unit is mounted on slide out rack for easy maintenance.
- Easy to mount plate casters (2 lockable) are standard with all units.

Toll Free: +1 (800) 373-8699 polarman@chefmindgroup.com Address: 1189S Jellick Ave, City of Industry, CA 91748













Toll Free: +1 (800) 373-8699 polarman@chefmindgroup.com Address: 1189S Jellick Ave, City of Industry, CA 91748

26 3/16" Reach-in Freezer all Stainless Steel

Model: PLM-19FS

·Certified to ANSI/NSF Standard 7



| MODEL | EXTERNAL DIMENSION (inches) | V/Hz/Ph | STORAGE CAPACITY Cu-ft | SHELF CAPACITY Sq-ft | TEMPERATURE | REFRIGERANT | AMPS | CORD LENGTH | NEMA PLUG | SHIPPING WEIGHT (lbs.) |
|----------|--------------------------------|-------------|---------------------------|-------------------------|-------------|-------------|------|----------------|--------------|---------------------------|
| PLM-19FS | 26 ¾ x 25 % 6 x 82 % 6 | 115V/60Hz/1 | 19 | 9.5 | -10°F | R290 | 5 | 8′ | 5-15P | 296 |













