

| Project name : |  |  |  |  |  |
|----------------|--|--|--|--|--|
| Location :     |  |  |  |  |  |
| Item#: QTY:    |  |  |  |  |  |
| Model#:        |  |  |  |  |  |

## 38 1/2" Reach-in Refrigerator all Stainless Steel

#### Model: PLM-35RS



- Tested to NSF Standard 7 requirements for open food storage.
- Interior cabinet is full stainless steel, floor with coved corners.
- Exterior cabinet construction consists of full stainless steel front and sides.
- Bottom mounted compressor for more efficient operation in coolest area of kitchen.
- Electronic thermostat with external digital LED display for accurate control and easy reading.
- Larger fan motors and blades for more efficient air flow ensuring faster recovery times.
- Efficient condensate hot gas loop built into condensate pan for energy saving evaporation of excess condensate water.
- Environmentally friendly R290 Hydrocarbon gas.
- 6 adjustable, heavy-duty expoxy coated wire shelves.
- Self closing doors that remain open at 90 degrees.
- Magnetic door gasket is removable and replaceable without tools.
- Lockable door with foamed-in-place recessed handle.
- Front accessible, bottom mounted condensing unit is mounted on slide out rack for easy maintenance.
- Easy to mount plate casters (2 lockable) are standard with all units.

Toll Free: +1 (800) 373-8699 polarman@chefmindgroup.com Address: 1189S Jellick Ave, City of Industry, CA 91748













Toll Free: +1 (800) 373-8699 polarman@chefmindgroup.com Address: 1189S Jellick Ave, City of Industry, CA 91748

# 38 1/2" Reach-in Refrigerator all Stainless Steel

### Model: PLM-35RS

### ·Certified to ANSI/NSF Standard 7



| MODEL    | EXTERNAL<br>DIMENSION (inches) | V/Hz/Ph     | STORAGE<br>CAPACITY Cu-ft | SHELF<br>CAPACITY Sq-ft | TEMPERATURE | REFRIGERANT | AMPS | CORD<br>LENGTH | NEMA<br>PLUG | SHIPPING<br>WEIGHT (lbs.) |
|----------|--------------------------------|-------------|---------------------------|-------------------------|-------------|-------------|------|----------------|--------------|---------------------------|
| PLM-35RS | 38 ½x32 ¼6x82 5/16             | 115V/60Hz/1 | 35                        | 20.1                    | 33°F~41°F   | R290        | 4.5  | 8′             | 5-15P        | 413                       |















