

Project name :								
Location :								
Item# : QTY : _								
Model#:								

53 15/16" Reach-in Refrigerator Stainless Steel Glass Door

Model: PLM-54RGS



- Tested to NSF Standard 7 requirements for open food storage.
- Interior cabinet is full stainless steel, floor with coved corners.
- Bottom mounted compressor for more efficient operation in coolest area of kitchen.
- Electronic thermostat with external digital LED display for accurate control and easy reading.
- Larger fan motors and blades for more efficient air flow ensuring faster recovery times.
- Efficient condensate hot gas loop built into condensate pan for energy saving evaporation of excess condensate water.
- Environmentally friendly R290 Hydrocarbon gas.
- 8 adjustable, heavy-duty expoxy coated wire shelves.
- Self closing doors that remain open at 90 degrees.
- Magnetic door gasket is removable and replaceable without tools.
- Lockable door with foamed-in-place recessed handle.
- Front accessible, bottom mounted condensing unit is mounted on slide out rack for easy maintenance.
- Easy to mount plate casters (2 lockable) are standard with all units.

Toll Free: +1 (800) 373-8699 polarman@chefmindgroup.com Address: 1189S Jellick Ave, City of Industry, CA 91748











Toll Free: +1 (800) 373-8699 polarman@chefmindgroup.com Address: 1189S Jellick Ave, City of Industry, CA 91748

53 15/16" Reach-in Refrigerator Stainless Steel Glass Door

Model: PLM-54RGS

·Certified to ANSI/NSF Standard 7



MODEL	EXTERNAL DIMENSION inch	V/Hz/Ph	STORAGE CAPACITY Cu-ft	SHELF CAPACITY Sq-ft	TEMPERATURE	REFRIGERANT	AMPS	CORD LENGTH	NEMA PLUG	SHIPPING WEIGHT (lbs.)
PLM-54RGS	53 ½ 6 X 31 % X 82 ½ 6	115V/60Hz/1	49	28.1	33°F-41°F	R290	4.5	8′	5-15P	598













